

ENEV RNP Z RWY 35 - RECOMMENDED CODING

| SN | PD | WI | Fly-over | °M (°T) | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|----------------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 010 | IF | LEGLU | - | - | -8.0 | - | - | - | A7000+ | - | - | - | 1.0 |
| 020 | TF | STETI | - | - | -8.0 | 8.0 | - | - | A7000+ | K220- | - | - | 1.0 |
| 010 | IF | MAXED | - | - | -8.0 | - | - | - | A7000+ | - | - | - | 1.0 |
| 020 | TF | STETI | - | - | -8.0 | 7.4 | - | - | A7000+ | K220- | - | - | 1.0 |
| 010 | IF | STETI | - | - | -8.0 | - | - | - | A7000+ | K220- | - | - | 1.0 |
| 020 | TF | EV712 | - | - | -8.0 | 10.6 | - | - | A3800+ | - | - | - | 1.0 |
| 030 | TF | EV710 | Y | - | -8.0 | 8.1 | - | - | - | - | -3.9/50 | - | 0.3 |
| 040 | TF | OKNOT | - | - | -8.0 | 7.9 | - | - | - | K185- | - | - | 1.0 |
| 050 | FA | OKNOT | - | 350 (357.6) | -8.0 | - | - | - | A3900+ | - | - | - | 1.0 |
| 060 | DF | OKNOT | - | - | -8.0 | - | - | L | - | - | - | - | 1.0 |
| 070 | HM | OKNOT | - | 170 (177.6) | -8.0 | 1 MIN | - | R | A5000 | K210- | - | - | 1.0 |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.