

ENVA RNP N RWY 09 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAV AID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	GISNE	-	-	-4.0	-	-	-	A4000+	-	-	-	0.3
20	TF	VA560	-	-	-4.0	3.9	-	-	A3000+	-	-	-	0.3
30	TF	VA541	-	-	-4.0	1.3	-	-	A2700+	K190-	-	-	0.3
40	RF	VA561	-	-	-4.0	3.3	-	L	A1700+	-	-	VA001 2.200	0.3
50	RF	VA549	-	-	-4.0	1.5	-	L	-	-	-3.0	VA001 2.200	0.3
60	TF	RW09	Y	-	-4.0	3.7	-	-	-	-	-3.0/50	-	0.3
70	TF	VA550	-	-	-4.0	2.9	-	-	-	-	-	-	0.3
80	RF	VA551	-	-	-4.0	1.9	-	L	-	K200-	-	VA002 3.700	1.0
90	TF	VA552	-	-	-4.0	5.0	-	-	-	-	-	-	1.0
100	RF	VA553	-	-	-4.0	18.2	-	L	-	-	-	VA005 5.748	1.0
110	TF	IRKIX	-	-	-4.0	16.3	-	-	A4000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.