

## ENVA RNP W RWY 09 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	UFDIF	-	-	-4.0	-	-	-	A4000+	-	-	-	1.0
20	TF	VA544	-	-	-4.0	4.1	-	-	A3000+	K190-	-	-	1.0
30	RF	VA546	-	-	-4.0	2.8	-	L	A2200+	-	-	VA003 3.283	0.3
40	RF	VA565	-	-	-4.0	1.7	-	R	A1700+	-	-	VA004 2.227	0.3
50	RF	VA549	-	-	-4.0	1.5	-	R	-	-	-3.0	VA004 2.227	0.3
60	TF	RW09	Y	-	-4.0	3.7	-	-	-	-	-3.0/50	-	0.3
70	TF	VA550	-	-	-4.0	2.9	-	-	-	-	-	-	0.3
80	RF	VA551	-	-	-4.0	1.9	-	L	-	K200-	-	VA002 3.700	1.0
90	TF	VA552	-	-	-4.0	5.0	-	-	-	-	-	-	1.0
100	RF	VA553	-	-	-4.0	18.2	-	L	-	-	-	VA005 5.748	1.0
110	TF	IRKIX	-	-	-4.0	16.3	-	-	A4000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.