

ENVA RNP W RWY 27 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ASKJA	-	-	-4.0	-	-	-	A4500+	K230-	-	-	1.0
20	TF	VA577	-	-	-4.0	2.4	-	-	A4000+	-	-	-	1.0
30	RF	VA574	-	-	-4.0	3.2	-	L	A3200+	-	-	VA009 3.200	0.7
40	RF	VA573	-	-	-4.0	3.3	-	L	A2200+	-	-	VA009 3.200	0.3
50	RF	VA570	-	-	-4.0	1.7	-	L	-	-	-3.4	VA009 3.200	0.3
60	TF	RW27	Y	-	-4.0	4.1	-	-	-	-	-3.4/50	-	0.3
70	TF	VA575	-	-	-4.0	10.5	-	-	-	-	-	-	1.0
80	RF	VA576	-	-	-4.0	10.6	-	R	-	K230-	-	VA010 3.300	1.0
90	TF	INSOD	-	-	-4.0	26.5	-	-	A4700+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.