

## ENZV RNP 033 (CAT H) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/FHPCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	IGSUF	-	-	-2.0	-	-	-	A1300+	-	-	-	1.0
20	TF	ZV447	-	-	-2.0	3.0	-	-	A1300+	-	-	-	1.0
30	TF	ZV451	-	-	-2.0	2.9	-	-	A1100+	-	-	-	1.0
40	TF	ZV452	Y	-	-2.0	2.8	-	-	-	-	-3.4/50	-	0.3
50	DF	ZV450	-	-	-2.0	-	-	L	A1400	-	-	-	1.0
60	TF	RUSSE	-	-	-2.0	13.7	-	-	A1400	-	-	-	1.0
70	HM	RUSSE	-	<sup>294</sup> (296.1)	-2.0	1MIN	-	L	A1400	K120-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.