

ENGM RNP O RWY 01L (AR) - RECOMMENDED CODING

| SN | PD | WI | Fly-over | °M (°T) | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|----|----|-------|----------|---------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 10 | IF | ERULO | - | - | -4.0 | - | - | - | A5000+ | K220- | - | - | 0.8 |
| 20 | TF | GM554 | - | - | -4.0 | 6.8 | - | - | A3500+ | K210- | - | - | 0.8 |
| 30 | RF | GM551 | - | - | -4.0 | 1.4 | - | R | A3000+ | - | - | GM007 3.400 | 0.3 |
| 40 | TF | GM552 | - | - | -4.0 | 1.9 | - | - | A2400+ | K205- | - | - | 0.3 |
| 50 | RF | GM553 | - | - | -4.0 | 2.0 | - | L | A1800+ | - | - | GM006 3.000 | 0.3 |
| 60 | TF | RW01L | - | - | -4.0 | 3.4 | - | - | - | - | -3.0/50 | - | 0.3 |
| 70 | TF | GM918 | Y | - | -4.0 | 21.1 | - | - | - | - | - | - | 1.0 |
| 80 | DF | VALPU | - | - | -4.0 | - | - | L | A5000+ | - | - | - | 1.0 |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.