

## ENGM RNP W RWY 01L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAV AID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ELVUN	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM550	-	-	-4.0	4.8	-	-	A4000+	K210-	-	-	1.0
30	RF	GM600	-	-	-4.0	1.9	-	L	A3500+	-	-	GM005 3.400	0.8
40	RF	GM551	-	-	-4.0	1.4	-	L	A3000+	-	-	GM005 3.400	0.3
50	TF	GM552	-	-	-4.0	1.9	-	-	A2400+	K205-	-	-	0.3
60	RF	GM553	-	-	-4.0	2.0	-	L	A1800+	-	-	GM006 3.000	0.3
70	TF	RW01L	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
80	TF	GM918	Y	-	-4.0	21.1	-	-	-	-	-	-	1.0
90	DF	VALPU	-	-	-4.0	-	-	L	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.