

ENGM RNP N RWY 19R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	RIRUT	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM601	-	-	-4.0	4.1	-	-	A4500+	-	-	-	1.0
30	TF	GM564	-	-	-4.0	3.1	-	-	A3300+	-	-	-	0.3
40	TF	GM563	-	-	-4.0	2.3	-	-	A2500+	-	-	-	0.3
50	RF	GM562	-	-	-4.0	2.4	-	R	A1800+	-	-	GM004 5.718	0.3
60	TF	RW19R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
70	TF	GM995	Y	-	-4.0	2.7	-	-	-	-	-	-	1.0
80	CF	GM996	Y	223 (227.0)	-4.0	-	-	R	-	-	-	-	1.0
90	DF	BAVAD	-	-	-4.0	-	-	R	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.