

ENGM RNP W RWY 19R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	EXWOD	-	-	-4.0	-	-	-	A5000+	K220-	-	-	0.8
020	TF	GM638	-	-	-4.0	1.8	-	-	A4600+	-	-	-	0.8
030	RF	GM635	-	-	-4.0	2.2	-	R	A4400+	-	-	GM018 4.982	0.8
040	RF	GM631	-	-	-4.0	1.7	-	R	A3600+	-	-	GM018 4.982	0.8
050	TF	GM636	-	-	-4.0	3.0	-	-	A2700+	K205-	-	-	0.3
060	RF	GM562	-	-	-4.0	3.0	-	R	A1800+	-	-	GM019 3.050	0.3
070	TF	RW19R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
080	TF	GM995	Y	-	-4.0	2.7	-	-	-	-	-	-	1.0
090	CF	GM996	Y	²²³ (227.0)	-4.0	-	-	R	-	-	-	-	1.0
100	DF	BAVAD	-	-	-4.0	-	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.