

## ENGM RNP S RWY 01R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	TAVRE	-	-	-4.0	-	-	-	A5000+	K220-	-	-	RNP 1.0
020	TF	GM559	-	-	-4.0	3.9	-	-	A3500+	-	-	-	RNP 1.0
030	RF	GM560	-	-	-4.0	2.4	-	R	-	-	-	GM008 3.900	RNP 0.3
040	RF	GM561	-	-	-4.0	1.8	-	L	A3000+	-	-	GM009 3.400	RNP 0.3
050	TF	GM557	-	-	-4.0	2.6	-	-	A2200+	K205-	-	-	RNP 0.3
060	RF	GM558	-	-	-4.0	1.4	-	R	A1800+	-	-	GM010 3.000	RNP 0.3
070	TF	RW01R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	RNP 0.3
080	TF	GM917	Y	-	-4.0	2.7	-	-	-	-	-	-	RNP 1.0
090	DF	NIDIM	Y	-	-4.0	-	-	R	A4000-	-	-	-	RNP 1.0
100	DF	INSUV	-	-	-4.0	-	-	R	A5000	-	-	-	RNP 1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.