

ENGM RNP W RWY 01R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	RUWOL	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	GM646	-	-	-4.0	4.5	-	-	A4000+	K210-	-	-	1.0
030	RF	GM645	-	-	-4.0	1.8	-	L	A3500+	-	-	GM005 3.400	0.8
040	RF	GM644	-	-	-4.0	2.5	-	R	A2500+	K185-	-	GM014 10.837	0.8
050	RF	GM558	-	-	-4.0	2.7	-	L	A1800+	-	-	GM017 2.473	0.8
060	TF	RW01R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
070	TF	GM917	Y	-	-4.0	2.7	-	-	-	-	-	-	1.0
080	DF	NIDIM	Y	-	-4.0	-	-	R	A4000-	-	-	-	1.0
090	DF	INSUV	-	-	-4.0	-	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.