

## ENGM RNP W RWY 19L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ZATCO	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	GM680	-	-	-4.0	2.8	-	-	-	-	-	-	1.0
030	RF	GM631	-	-	-4.0	1.8	-	R	A4000+	-	-	GM030 4.982	0.8
040	TF	GM679	-	-	-4.0	3.0	-	-	A3000+	K195-	-	-	0.4
050	RF	GM652	-	-	-4.0	0.8	-	R	-	-	-	GM029 2.831	0.3
060	TF	GM678	-	-	-4.0	2.0	-	-	A2200+	-	-	-	0.3
070	RF	GM654	-	-	-4.0	1.8	-	R	-	-	-3.0	GM028 2.617	0.3
080	TF	RW19L	-	-	-4.0	2.8	-	-	-	-	-3.0/50	-	0.3
090	TF	GM655	-	-	-4.0	2.8	-	-	-	-	-	-	1.0
100	RF	GM670	-	-	-4.0	8.0	-	L	-	K250-	-	GM022 4.500	1.0
110	TF	GM942	Y	-	-4.0	14.1	-	-	-	-	-	-	1.0
120	DF	TITLA	-	-	-4.0	-	-	L	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.