

ENRA RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	MAGAP	-	-	-6.0	-	-	-	A5000+	-	-	-	1.0
20	TF	PETOK	-	-	-6.0	6.0	-	-	A5000+	-	-	-	1.0
10	IF	LORDO	-	-	-6.0	-	-	-	A5000+	-	-	-	1.0
20	TF	PETOK	-	-	-6.0	6.0	-	-	A5000+	-	-	-	1.0
10	IF	PETOK	-	-	-6.0	-	-	-	A5000+	-	-	-	1.0
20	TF	ODNOS	-	-	-6.0	9.2	-	-	A5000+	-	-	-	1.0
10	IF	SUBIT	-	-	-6.0	-	-	-	A5000+	-	-	-	1.0
20	TF	GILKO	-	-	-6.0	6.0	-	-	A5000+	-	-	-	1.0
30	TF	ODNOS	-	-	-6.0	4.2	-	-	A5000+	-	-	-	1.0
40	TF	RA501	-	-	-6.0	6.2	-	-	A3100+	-	-	-	1.0
50	TF	RA502	Y	-	-6.0	7.7	-	-	-	-	-3.3	-	0.3
60	CA	-	-	066 (071.8)	-6.0	-	-	-	A2100	K130-	-	-	1.0
70	DF	ODNOS	-	-	-6.0	-	-	L	-	-	-	-	1.0
80	HM	ODNOS	-	074 (079.6)	-6.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.