

ENEV RNP Z RWY 35 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	LEGLU	-	-	-8.0	-	-	-	A7000+	-	-	-	1.0
020	TF	STETI	-	-	-8.0	8.0	-	-	A7000+	K220-	-	-	1.0
010	IF	MAXED	-	-	-8.0	-	-	-	A7000+	-	-	-	1.0
020	TF	STETI	-	-	-8.0	7.4	-	-	A7000+	K220-	-	-	1.0
010	IF	STETI	-	-	-8.0	-	-	-	A7000+	K220-	-	-	1.0
020	TF	EV712	-	-	-8.0	10.6	-	-	A3800+	-	-	-	1.0
030	TF	EV710	Y	-	-8.0	8.1	-	-	-	-	-3.9/50	-	0.3
040	TF	OKNOT	-	-	-8.0	7.9	-	-	-	K185-	-	-	1.0
050	FA	OKNOT	-	350 (357.6)	-8.0	-	-	-	A3900+	-	-	-	1.0
060	DF	OKNOT	-	-	-8.0	-	-	L	-	-	-	-	1.0
070	HM	OKNOT	-	170 (177.6)	-8.0	1 MIN	-	R	A5000	K210-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.