

ENGM RNP S RWY 01L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	MONCI	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
20	TF	GM621	-	-	-4.0	4.0	-	-	A4200+	-	-	-	1.0
30	RF	GM560	-	-	-4.0	1.6	-	R	A3800+	K210-	-	GM012 3.900	0.6
40	RF	GM622	-	-	-4.0	3.3	-	L	A2800+	-	-	GM009 3.400	0.3
50	TF	GM623	-	-	-4.0	0.7	-	-	A2600+	K205-	-	-	0.3
60	RF	GM553	-	-	-4.0	2.7	-	R	A1800+	-	-	GM013 3.000	0.3
70	TF	RW01L	Y	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
80	TF	GM918	Y	-	-4.0	21.1	-	-	-	-	-	-	1.0
90	DF	VALPU	-	-	-4.0	-	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.