

ENGM RNP N RWY 19L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AZZIT	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	GM673	-	-	-4.0	4.5	-	-	A4000+	-	-	-	1.0
030	RF	GM672	-	-	-4.0	3.4	-	R	A3000+	-	-	GM027 4.5	0.5
040	TF	GM671	-	-	-4.0	2.8	-	-	A2100+	-	-	-	0.3
050	RF	GM473	-	-	-4.0	2.3	-	L	-	-	-3.0	GM025 2.733	0.3
060	TF	RW19L	Y	-	-4.0	2.0	-	-	-	-	-3.0/50	-	0.3
070	TF	GM655	-	-	-4.0	2.8	-	-	-	-	-	-	1.0
080	RF	GM670	-	-	-4.0	8.0	-	L	-	K250-	-	GM022 4.500	1.0
090	TF	GM942	Y	-	-4.0	14.1	-	-	-	-	-	-	1.0
100	DF	TITLA	-	-	-4.0	-	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.