

ENGM RNP Z RWY 19L - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	TITLA	-	-	-4.0	-	-	-	A5000+	K220	-	-	1.0
020	TF	OSPAD	-	-	-4.0	5.0	-	-	A4000+	K200-	-	-	1.0
010	IF	BAVAD	-	-	-4.0	-	-	-	A5000+	K220	-	-	1.0
020	TF	OSPAD	-	-	-4.0	6.0	-	-	A4000+	K200-	-	-	1.0
030	TF	XIVTA	-	-	-4.0	3.8	-	-	A3500+	-	-	-	1.0
040	TF	RW19L	Y	-	-4.0	8.7	-	-	-	-	-3.0/50	-	0.3
050	TF	GM908	Y	-	-4.0	3.2	-	-	-	-	-	-	1.0
060	CF	GM941	-	102 (106.0)	-4.0	-	-	L	A3000	-	-	-	1.0
070	TF	GM942	Y	-	-4.0	6.8	-	-	A5000	-	-	-	1.0
080	DF	TITLA	-	-	-4.0	-	-	-	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: The use of SBAS/GNSS geometric altitude as a source of altitude for approaches to LNAV/VNAV minima is permitted only for aircraft specifically certified for this type of operation. See “EASA CS ACNS.C.PBN.560” for additional information.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.