

ENCN RNP W RWY 21 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	OFTIP	-	-	-4.0	-	-	-	A3500+	-	-	-	1.0
020	TF	CN837	-	-	-4.0	2.7	-	-	A3500+	K220-	-	-	1.0
030	RF	CN835	-	-	-4.0	2.1	-	R	A3000+	-	-	CN848 6.5	0.6
040	RF	CN833	-	-	-4.0	2.1	-	R	A2500+	-	-	CN845 2.67	0.6
050	TF	CN831	-	-	-4.0	1.6	-	-	A2100+	-	-	-	0.6
060	RF	CN830	-	-	-4.0	2.4	-	R	A1400+	-	-	CN846 2.55	0.4
070	TF	RW21	Y	-	-4.0	3.5	-	-	-	-	-3.5/50	-	0.3
080	TF	INRAT	-	-	-4.0	13.0	-	-	A3000+	-	-	-	1.0
090	HM	INRAT	-	031 (034.9)	-4.0	1 MIN	-	R	A3000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.