

ENKB RNP E RWY 25 (AR) - RECOMMENDED CODING

| SN  | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|-----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 010 | IF | EZUNE | -        | -           | -3.0    | -         | -          | -  | A5000+   | K230-      | -                | -                      | 0.6      |
| 020 | TF | KB918 | -        | -           | -3.0    | 2.6       | -          | -  | A4200+   | -          | -                | -                      | 0.6      |
| 030 | TF | KB917 | -        | -           | -3.0    | 3.9       | -          | -  | A3000+   | -          | -                | -                      | 0.6      |
| 040 | TF | KB914 | -        | -           | -3.0    | 3.2       | -          | -  | A1800+   | -          | -                | -                      | 0.5      |
| 050 | TF | KB913 | -        | -           | -3.0    | 1.2       | -          | -  | -        | -          | -3.5             | -                      | 0.3      |
| 060 | RF | KB912 | -        | -           | -3.0    | 1.0       | -          | L  | -        | -          | -3.5             | KB004 5.000            | 0.3      |
| 070 | TF | RW25  | Y        | -           | -3.0    | 2.0       | -          | -  | -        | -          | -3.5/50          | -                      | 0.3      |
| 080 | TF | KB909 | -        | -           | -3.0    | 7.0       | -          | -  | -        | -          | -                | -                      | 1.0      |
| 090 | RF | KB910 | -        | -           | -3.0    | 2.0       | -          | R  | -        | -          | -                | KB005 6.400            | 1.0      |
| 100 | TF | KB422 | -        | -           | -3.0    | 2.1       | -          | -  | -        | -          | -                | -                      | 1.0      |
| 110 | RF | KB911 | -        | -           | -3.0    | 7.5       | -          | R  | A3000+   | K230-      | -                | KB006 3.230            | 1.0      |
| 120 | TF | APTAT | -        | -           | -3.0    | 11.6      | -          | -  | A5000    | -          | -                | -                      | 1.0      |
| 130 | HM | APTAT | -        | 157 (159.7) | -3.0    | 1 MIN     | -          | L  | A5000    | K230-      | -                | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.