

ENTC RNP S RWY 18 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	OSHO	-	-	-10.0	-	-	-	A6000+	-	-	-	1.0
020	TF	TC554	-	-	-10.0	4.9	-	-	A4600+	-	-	-	1.0
030	TF	TC553	-	-	-10.0	3.1	-	-	A3700+	K210-	-	-	1.0
040	RF	TC551	-	-	-10.0	4.1	-	L	A2100+	-	-	TC012 2.48	1.0
050	RF	TC542	-	-	-10.0	2.6	-	L	-	-	-3.7	TC012 2.48	0.3
060	TF	RW18	Y	-	-10.0	2.6	-	-	-	-	-3.7/50	-	0.3
070	TF	TC505	-	-	-10.0	6.1	-	-	-	-	-	-	1.0
080	RF	TC516	-	-	-10.0	2.6	-	L	-	-	-	TC003 5.0	1.0
090	TF	TC506	Y	-	-10.0	11.1	-	-	-	-	-	-	1.0
100	DF	ETUTU	-	-	-10.0	-	-	R	A5000	-	-	-	1.0
110	HM	ETUTU	-	003 (012.9)	-10.0	1 MIN	-	L	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.