

ENTC RNP O RWY 36 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ELLEF	-	-	-10.0	-	-	-	A5000+	-	-	-	0.8
020	TF	TC561	-	-	-10.0	3.8	-	-	A4000+	-	-	-	0.8
030	TF	TC560	-	-	-10.0	2.3	-	-	A3400+	-	-	-	0.8
040	RF	TC559	-	-	-10.0	2.5	-	L	A2400+	-	-	TC018 4.97	0.8
050	RF	TC555	-	-	-10.0	2.5	-	L	A1400+	-	-	TC018 4.97	0.8
060	TF	RW36	Y	-	-10.0	3.4	-	-	-	-	-3.7/50	-	0.3
070	TF	TC527	-	-	-10.0	3.0	-	-	-	-	-	-	0.3
080	TF	TC528	-	-	-10.0	4.0	-	-	-	-	-	-	1.0
090	RF	TC529	-	-	-10.0	4.6	-	L	-	-	-	TC006 3.03	1.0
100	TF	TC530	-	-	-10.0	2.0	-	-	-	-	-	-	1.0
110	RF	TC531	-	-	-10.0	4.1	-	L	-	K230-	-	TC007 3.03	1.0
120	TF	OSRAD	-	-	-10.0	8.5	-	-	A5000	-	-	-	1.0
130	HM	OSRAD	-	196 (206.0)	-10.0	1 MIN	-	R	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.