

ENHF GLS Z RWY 22 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	UNGEP	-	-	-14.0	-	-	-	A3000+	-	-	-	1.0
020	TF	MAPUB	-	-	-14.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	ADVOR	-	-	-14.0	-	-	-	A3300+	-	-	-	1.0
020	TF	MAPUB	-	-	-14.0	5.0	-	-	A3000+	-	-	-	1.0
010	IF	MAPUB	-	-	-14.0	-	-	-	A3000+	-	-	-	1.0
020	TF	HF401	-	-	-14.0	4.7	-	-	A3000+	-	-	-	1.0
030	TF	RW22	-	-	-14.0	6.5	-	-	-	-	-3.9/50	-	-
040	TF	INSEN	-	-	-14.0	15.4	-	-	-	-	-	-	1.0
050	HM	INSEN	-	042 (056.0)	-14.0	1 MIN	-	L	A4600	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
112.600 MHZ	704036.02N 0233936.15E	GND STN, VHF Antenna