

ENCN RNP E RWY 21 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	DELWO	-	-	-4.0	-	-	-	A3500+	-	-	-	1.0
020	TF	CN834	-	-	-4.0	2.7	-	-	A3000+	K220-	-	-	1.0
030	RF	CN832	-	-	-4.0	2.5	-	L	A2400+	-	-	CN847 5.5	0.5
040	RF	CN830	-	-	-4.0	4.2	-	L	A1400+	-	-	CN843 2.64	0.4
050	TF	RW21	Y	-	-4.0	3.5	-	-	-	-	-3.5/50	-	0.3
060	TF	INRAT	-	-	-4.0	13.0	-	-	A3000+	-	-	-	1.0
070	HM	INRAT	-	031 (034.9)	-4.0	1 MIN	-	R	A3000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.