

ENKB RNP S RWY 07 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	KILIZ	-	-	-3.0	-	-	-	A5000+	K230-	-	-	0.3
020	TF	KB907	-	-	-3.0	2.5	-	-	A4400+	-	-	-	0.3
030	TF	KB906	-	-	-3.0	3.8	-	-	A3000+	-	-	-	0.3
040	TF	KB905	-	-	-3.0	1.9	-	-	A2300+	-	-	-	0.3
050	TF	KB904	-	-	-3.0	1.6	-	-	A1800+	-	-	-	0.3
060	RF	KB903	-	-	-3.0	2.6	-	R	-	-	-3.0	KB001 2.08	0.3
070	TF	RW07	Y	-	-3.0	2.4	-	-	-	-	-3.0/50	-	0.3
080	TF	KB901	-	-	-3.0	1.8	-	-	-	-	-	-	0.3
090	RF	KB902	-	-	-3.0	4.9	-	L	-	K220-	-	KB002 2.45	1.0
100	TF	APTAT	-	-	-3.0	9.9	-	-	A5000	-	-	-	1.0
110	HM	APTAT	-	157 (159.7)	-3.0	1 MIN	-	L	A5000	K230-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.