

INSTRUMENT APPROACH CHART - ICAO

177°

3₉

087°

3₂

357°

267°

1₇

MSA 25 NM TOR

ATIS: 119.080

APP: 134.055 124.355

TWR: 118.655

GND: 126.180

AD ELEV: 286

THR ELEV: 282

HGT RELATED TO THR 17

CIRCLING HGT RELATED TO AD ELEV

DIST IN NM. ELEV, ALT AND HGT IN FT

SCALE 1:500 000

VAR 5°E (2025)

SANDEFJORD
TORP

ILS or LOC RWY 17 CAT II

TRANSITION ALTITUDE
7000

DIST TO TRP	9	8	7	6	5	4	3	2
ALT (HGT)	-	2850 (2568)	2530 (2248)	2210 (1928)	1890 (1608)	1570 (1288)	1250 (968)	930 (648)

CAT OF ACFT		A	B	C	D
OCA (H) STRAIGHT- IN	CAT I	426 (144)	435 (153)	445 (163)	455 (173)
	CAT II	(53)	(62)	(75)	(87)
	LOC	740 (459)			
CIRCLING		840 (554)	880 (594)	980 (694)	1000 (714)

NOTE:

CHANGES: MAG VAR. RWY ID. EDITORIALS.

ATS AIRSPACE CLASSIFICATION: REF ENR 1.4

Avinor

11 JUN 2026