

ENAT RNP W RWY 11 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	IVKOD	-	-	-13.0	-	-	-	A5000+	K230-	-	-	0.4
020	TF	AT602	-	-	-13.0	2.4	-	-	A5000+	-	-	-	0.4
030	TF	AT603	-	-	-13.0	2.9	-	-	A4000+	-	-	-	0.4
040	TF	AT604	-	-	-13.0	2.5	-	-	A3100+	-	-	-	0.4
050	RF	AT607	-	-	-13.0	4.0	-	R	A1700+	K160-	-	AT002 3.800	0.3
060	TF	RW11	Y	-	-13.0	4.4	-	-	-	-	-3.5/50	-	0.3
070	TF	AT609	-	-	-13.0	1.0	-	-	-	-	-	-	0.3
080	RF	AT610	-	-	-13.0	2.1	-	R	-	K190-	-	AT004 3.240	0.3
090	TF	AT611	-	-	-13.0	4.4	-	-	-	-	-	-	0.3
100	RF	AT612	-	-	-13.0	1.4	-	R	-	-	-	AT005 10.000	0.7
110	TF	ATMOM	-	-	-13.0	1.9	-	-	A5000	-	-	-	0.7
120	HM	ATMOM	-	143 (156.2)	-13.0	1 MIN	-	R	A5000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.