ENBO RNP X RWY 07 (LPV only) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG. VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	OKNED	-	-	-6.0	-	-	-	A4500+	K220-	-	-	1.0
20	TF	RIPDO	-	-	-6.0	6.3	-	-	A2000+	K200-	-	-	1.0
10	IF	ODAGO	-	-	-6.0	-	-	-	A4000+	K220-	-	-	1.0
20	TF	RIPDO	-	-	-6.0	4.8	-	-	A2000+	K200-	-	-	1.0
10	IF	ROTOT	-	-	-6.0	-	-	-	A4000+	-	-	-	1.0
20	TF	RIPDO	-	-	-6.0	5.4	-	-	A2000+	K200-	-	-	1.0
30	TF	BO530	-	-	-6.0	3.7	-	-	A1400+	-	-	-	1.0
40	TF	RW07	Y	-	-6.0	4.2	-	-	-	-	-3.0/50	-	-
50	TF	BO531	Y	-	-6.0	1.0	-	-	-	-	-	-	1.0
60	DF	BO532	-	-	-6.0	-	-	R	-	K205-	-	-	1.0
70	TF	BO533	Y	-	-6.0	10.1	-	-	-	K130- /K230-	-	-	1.0
80	DF	BO534	-	-	-6.0	-	-	R	-	-	-	-	1.0
90	TF	ODAGO	-	-	-6.0	12.6	-	-	-	-	-	-	1.0
100	HM	ODAGO	-	161 (167.5)	-6.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	**0**	**LTP/FTP ellipsoidal height**	**37.2**
SBAS provider	**1**	**FPAP latitude**	**671618.7790N**
Airport identifier	**ENBO**	**FPAP longitude**	**0142350.6510E**
Runway	**RW07**	**Threshold crossing height**	**50**
Approach performance designator	**0**	**TCH units**	**FT**
Route indicator	**X**	**Glide path angle**	**3**
Reference path data selector	**0**	**Course width at threshold**	**105**
Reference path identifier	**E07A**	**Length offset**	**0**
LTP/FTP latitude	**671559.7575N**	**Horizontal alert limit (HAL)**	**40**
LTP/FTP longitude	**0142002.7065E**	**Vertical alert limit (VAL)**	**50**
	PRECISION APPROACH PATH CRC REMAINDER		**6BC69517**