

ENBV GLS RWY 06 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	KUKIX	-	-	-16.0	-	-	-	A7000+	-	-	-	1.0
020	TF	BV503	-	-	-16.0	5.0	-	-	A5000+	-	-	-	1.0
010	IF	OLPID	-	-	-16.0	-	-	-	A5000+	-	-	-	1.0
020	TF	BV503	-	-	-16.0	5.0	-	-	A5000+	-	-	-	1.0
010	IF	ENUMA	-	-	-16.0	-	-	-	A7000+	-	-	-	1.0
020	TF	BV503	-	-	-16.0	5.0	-	-	A5000+	-	-	-	1.0
030	TF	UMPEP	-	-	-16.0	4.8	-	-	A4000+	-	-	-	1.0
040	TF	RW06	Y	-	-16.0	9.5	-	-	-	-	-3.9/49	-	-
050	TF	ASMEL	-	-	-16.0	9.8	-	-	-	-	-	-	1.0
060	HM	ASMEL	-	239 (255.2)	-16.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
114.300 MHZ	705222.33N 0290211.27E	GND STN, VHF Antenna