

ENKB RNP Z RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	INKEV	-	-	-3.0	-	-	-	A4500+	K230-	-	-	1.0
020	TF	GUDVA	-	-	-3.0	5.0	-	-	A4300+	K220-	-	-	1.0
010	IF	DODUN	-	-	-3.0	-	-	-	A4500+	K230-	-	-	1.0
020	TF	GUDVA	-	-	-3.0	5.0	-	-	A4300+	K220-	-	-	1.0
010	IF	GUDVA	-	-	-3.0	-	-	-	A4300+	K220-	-	-	1.0
020	TF	UPKEP	-	-	-3.0	4.0	-	-	A3500+	-	-	-	1.0
030	TF	KB780	Y	-	-3.0	8.8	-	-	-	-	-3.5/50	-	0.3
040	TF	KB422	Y	-	-3.0	11.0	-	-	-	-	-	-	1.0
050	DF	APTAT	-	-	-3.0	-	-	R	-	-	-	-	1.0
060	HM	APTAT	-	157 (159.6)	-3.0	1 MIN	-	L	A5000	K230-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: GUDVA holding not included in standard APCH transitions.